

Date: Tuesday, 13/05/2008 11:08:50 AM
 User: Julie Lecocq

Process Sheet

Customer	: CU-DAR001 Dart Helicopters Services	Drawing Name	: LUG BRACKET
Job Number	: 39241		
Estimate Number	: 10010		
P.O. Number	:	Part Number	: D27353
This Issue	: 13/05/2008 S.O. No. :	Drawing Number	: D2735 REV C
Prsht Rev.	: NC	Project Number	: N/A
First Issue	: // Type : SMALL /MED FAB	Drawing Revision	: C
Previous Run	: 38033	Material	:
Written By	:	Due Date	: 30/05/2008 Qty: 40 Um: Each
Checked & Approved By	: <u>JUD 08.5.13</u>		
Comment	: Est Rev: C Removed from 9 Digit 05-10-25 JLM Est. C 06.07.21 waterjet EC		

Additional Product

Job Number:



Seq. #:	Machine Or Operation:	Description :
---------	-----------------------	---------------

1.0	M1010S125	1010-1025 sheet .125
-----	-----------	----------------------



Comment: Qty.: 0.1733 sf(s)/Unit Total : 6.9300 sf(s)

1010-1025 sheet .125

batch: 107513 HB 8-5-21

2.0	WATER JET	FLOW WATER JET
-----	-----------	----------------



Comment: FLOW WATER JET

1-Cut as per Dwg D2735

Dwg Rev: C

Prog Rev: C

2-Deburr if necessary

HB 8-5-21

(45)

HB 8-5-21

3.0	QC2	INSPECT PARTS AS THEY COME OFF MACHINE
-----	-----	--



Comment: INSPECT PARTS AS THEY COME OFF MACHINE

4.0	QC8	SECOND CHECK
-----	-----	--------------



Comment: SECOND CHECK

S 08/05/21 x 45 water

5.0	BRAKE NC	NC BRAKE
-----	----------	----------



Comment: NC BRAKE

1-Form D2735-1 as per Dwg D2735. Use CNC Brake Jig DT8204

2-Deburr if required.

S 08/05/21 x 45

(45)

Dart Aerospace Ltd

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Tuesday, 13/05/2008 11:08:50 AM
User: Julie Lecocq

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: LUG BRACKET

Job Number: 39241

Part Number: D27353

Job Number:



Seq. #:

Machine Or Operation:

Description :

6.0

QC5

INSPECT WORK TO CURRENT STEP



counted

Comment: INSPECT WORK TO CURRENT STEP

S 08/05/28 (FY5)

7.0

PACKAGING 1

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: _____

SD267

08/05/28

(45)

8.0

QC21

FINAL INSPECTION/W/O RELEASE



08/05/29

Comment: FINAL INSPECTION/W/O RELEASE

Job Completion



MF 08-05-29

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

QA: N/C Closed: _____ Date: _____


NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries




DESIGN <i>[Signature]</i>	DRAWN BY <i>[Signature]</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>[Signature]</i>	APPROVED <i>KE</i>	DRAWING NO. D2735	REV. C SHEET 1 OF 2
DATE 98.12.14		TITLE LUG BRACKET	SCALE 2:3
A	97.12.14	NEW ISSUE	
B	98.10.23	UPDATE MATERIAL (TSR A1114)	
C	98.12.14	REMOVE TOOLING HOLES (TSR A1040)	

RELEASED
98.12.14 DS



D2735-1 FLAT PATTERN
SYMMETRIC ABOUT BOTH CENTRE-LINES (CL)




D2735-3 FLAT PATTERN
SYMMETRIC ABOUT CENTRE-LINE (CL)

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 39241

DART

DESIGN <i>PH</i>	DRAWN BY <i>PH</i>	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
CHECKED <i>CP</i>	APPROVED <i>KE</i>	DRAWING NO. D2735	REV. C SHEET 2 OF 2
DATE 98.12.14	TITLE LUG BRACKET		SCALE 2:3

RELEASED
98.12.14 DS**D2735-1 AND D2735-3 BEND DETAIL**

D2735-1 AND D2735-3 SHOULD BE BENT TO WITHIN 0.010 OF THE OUTSIDE PROFILE OF THE D2500-1 EXTRUSION IN THE AREAS INDICATED 'X' ABOVE.

GENERAL NOTES

MATERIAL: ASTM A36/A366/A569/A570 OR AISI 1010-1025 STEEL
0.125 THICK (11 GAUGE)
MIN. ULTIMATE TENSILE STRENGTH = 42 ksi
MIN. YIELD TENSILE STRENGTH = 28 ksi

TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED
ALL DIMENSIONS ARE IN INCHES

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 39241